


**FIELD OF USE**

Safety helmet for industry or for electricians.

**CHARACTERISTICS**

- ABS helmet, no ventilation, ultra light weight.
- Low density – high pressure polyethylene head rim.
- Deformable helmet in case of shock, equipped with a “gutter”.
- Adjustable size from 53 to 62 cm, adjustment of head rim at 5 mm intervals.
- 4 points textile head base, adjustable for a perfect fit.
- Frontal trimming.
- In compliance with the standards:
  - EN 397.  
Use at very low temperature: - 30°C.  
Electrical insulation: 440 V AC; DIN EN 397 1000 V.  
Protection against ejections of molten metal (MM).
  - EN 50 365  1000 V. Electrically insulating helmet for low voltage uses.
  - ANSI Z 89.1 20000 V.

REFERENCE	DESIGNATION	WEIGHT (kg)
MO-182/1-B	Safety helmet for electrician, color white	0,3
MO-182/1-R	Safety helmet for electrician, color red	0,3
MO-182/1-J	Safety helmet for electrician, color yellow	0,3

**OPTIONS**

You can complete your equipment with the following :

- MS-118 : Headlamp with adjustable focus.
- MS-121 : 3 LEDs headlamp.
- MS-127 : 5 LEDs headlamp
- M-95-864 : hooks set to fix the headlamp on the helmet
- MO-184 : Face shield.